

B. Group 2

1. Elevator Nos.: P1- P5, & P8 - P10
Usage: Passenger, Service
Location: Building Core
Type: 8 Gearless double wrap traction elevators
Capacity and Speed: 4000# at 500 fpm
Travel: 128 Feet - 4 inches.
Stops and Openings: 12 Stops, 12 Openings
Manufacturer: Otis
Operation: Autotronic Unlimited
Control: Serge
Machine: Otis #70 DWT
Motor: Otis Size 70, 190 Volts, 127 RPM, 41 HP
Controller: Serge
Main Current: 208 Volts A.C., 3 Phase 60 Cycle
Operating Current: 120 Volts A.C.
Starter: Integral
Ropes: (Hoisting): (5)- ½ " of 8 X 19 Steel
Roping: 2:1
Governor: Otis 7063 Governor Rope: (1)- 1/2" 8 X 19 Steel Car & Counterweight
Buffers: Oil with 28" Stroke Safeties: 14D Door Operator (Power): 6970A Operator
Hoistway & Car Doors: 2 Speed Side Opening 44" clear Opening Door Closures:
Otis 42A
Door Hangers: AU
Compensation Ropes: (5) 5/8"
Car & Counterweight guides: Roller
Brakes: #70 Otis
Additional Features:
 1. Special Emergency Service - Phase I & II
 2. Top of Car Inspection
 3. Machine Room Indicator Panel
 4. Electronic Touch Buttons
 5. Nudging feature on doors
 6. Safety shoe and Double Beam Light Ray
 7. Emergency Power Generation Dispatch System
 8. Key Operated Access from Hall
 9. Load Weighting Device
2. Elevators Nos.: S6 & S7
Usage: Service
Location: Building Core
Type: (2) Gearless Double Wrap Traction Elevators Manufacturer: Otis
Capacity & Speed: 5000# at 500 fpm
Travel: 141 feet 4 inches
Stops & Openings: 13 Stops, 13 Openings
Operation: Autotronic Unlimited
Control: Serge

Machine: Otis #72 DWT
Motor: Otis Size 72, 210 Volts A.C. 127 rpm 52 hp
Controller: Serge
Main Current: 208 Volts A.C., 3 Phase, 60 Cycle
Operating Current: 208 Volts A.C., 3 Phase, 60 Cycle
Starter: Integral
Ropes (Hoisting): (5)- 1/2" of 8 X 19 Steel
Roping: 2:1
Governor: Otis 7063
Governor Rope: (1) - 1/2" of 8 X 19 Steel
Car & Counterweight Buffers: Oil with 28" Stroke
Safeties: 14D
Door Operator (Power): 6970A Operator
Hoistway & Car Doors: 2 Speed Side Opening 56" Clear Opening Door Closures: 42A
Door Hangers: AU
Compensation Ropes: (5) - 5/8"
Car and Counterweight
Guides: Roller
Brakes: #72
Additional Features:

1. Special Emergency Service - Phases I & II
2. Top of Car Inspection
3. Machine Room Indicator Panel
4. Electronic Touch Buttons
5. Safety Shoe and Double Beam Light Ray
6. Emergency power Generation Dispatch System
7. Key Operated Access from Hall
8. Load Weighing Device
9. Special Emergency Hospital Priority Service from All Floors

3. Elevators Nos.: P 11 & P 12
Usage: Passenger
Type: Geared Traction Elevators
Location: Outpatient Clinic - Wing E
Travel: 23 feet 10 inches.
Stops & Openings: 3 Stops, and 3 Openings Capacity & Speed: 4000# at 350 fpm
Manufacturer: Hollister Whitney
Operation: Duplex Selective Collection 1 - G.A.L. Control: Unit Multi-Voltage
Machine: #63 Hollister Whitney
Motor: 40 hp Imperial
Controller: G.A.L.
Roping: 1:1
Ropes (Hoisting): (5)- 5/8", 8 x 19 Steel
M.G. Set: 30KW Imperial
Car & Counterweight Guides: Roller

Car & Counterweight Buffers: Oil

Power Supply: 480 Volts, 3 Phase, 60 Cycle Governor: Ball Governor

Governor Rope: (1) 1/2" 8 X 19 Steel